

PAT-NO: JP411222206A
DOCUMENT-IDENTIFIER: JP 11222206 A
TITLE: SUPERPOSING METHOD FOR BUILDING MATERIAL
PUBN-DATE: August 17, 1999

INVENTOR-INFORMATION:

NAME	COUNTRY
YOSHIDA, SHIGEO	N/A
MATSUSHITA, KAZUMI	N/A
YONEDA, TSUGUO	N/A
KITAGAWA, SATOSHI	N/A
KUMAGAI, HITOSHI	N/A

ASSIGNEE-INFORMATION:

NAME	COUNTRY
NATL HOUSE IND CO LTD	N/A

APPL-NO: JP10034079
APPL-DATE: January 30, 1998

INT-CL (IPC): B65B033/00

ABSTRACT:

PROBLEM TO BE SOLVED: To improve working efficiency in a superposing method for building materials, automate easily the superposing method by machine installation, and achieve the effective utilization of material resources.

SOLUTION: A plurality of building materials 1 such as exterior materials and roof tiles are superposed on one another in a state that a releasable elastic pressure-sensitive adhesive 2 such as a hot-melt adhesive is interposed therebetween. Examples of the building materials 1 include inorganic exterior materials such as siding boards, roof tile members, glass members,

ceiling
materials such as rock wool boards, floor materials for precious
wood-woody
floors, etc., interior wall materials such as precious wood veneer
boards, and
others. Rubber-based, urethane resin-based, silicone resin-based,
modified
silicone resin-based and like pressure-sensitive adhesives can be
adopted as
the releasable elastic pressure-sensitive adhesive 2. In order to
make the
pressure-sensitive adhesive releasable, these various pressure-
sensitive
adhesives are subjected to heat treatment or chemical treatment and
are used by
reducing pressure- sensitive performance to a predetermined level.
This level
of the pressure- sensitive performance is decided by a surface state
of each
building material 1 to be used.

COPYRIGHT: (C)1999,JPO